




Data Sheet (EN)

Translation of the german original

Designation, Model:	Order number:
Diaphragm pumps, chemical resistant Models: MPC 303 Z 230v	415722
MPC 603 E 230v	415721

Figure:	Description:	
	The diaphragm pump consists of a pump body and a drive motor. The pump casing contains the drive unit and two pump heads. Each pump head contains a moulded diaphragm and two work valves. Both pump heads are arranged opposite each other. The pump heads are driven via an eccentric shaft with a connecting rod.	

Application:	${\it Materials ot the medium-affecting pump parts:}$	
The Diaphragm pumps MPC 303 Z and MPC 603 E are intended for:		
Pumping and compressing neutral and aggressive gases and vapours according to the resistance of the indicated materials. Generating a vacuum down to an ultimate pressure < 5 mbar. Use in physical and chemical laboratories in trade and industry. Use for vacuum filtration, vacuum distillation and vacuum drying, and other vacuum technology applications.	PTFE - Form moulded diaphragms PTFE - Pump heads PTFE - Vacuum hose PEEK - Valves EPDM - Seals PVDF - Screw fittings	







Data Sheet (EN)

Translation of the german original

Technical data:				
Parameter	MPC 603 E	MPC 303 Z	Unit	
Pump stages	1	2	-	
	4.0 / 4.4	2.0 / 2.2	m³/h	
Pumping speed DIN 28432	66 / 73	33 / 36	1 / min	
Ultimate pressure	< 55	< 5	mbar	
Ultimate pressure with gas ballast	80	8	mbar	
Max. Inlet-/Outlet pressure	≤110	00	mbar	
Intake port	Small flange DN 16 KF optionally enclosed Hose nozzle DN 8 for hose inside diameter 8 mm		-	
Exhaust port	Hose nozzle DN 8 for hose inside diameter 8 mm			
Ambient temperature	+ 10 to + 40		°C	
Max. Operating gas temperature	≤ + 40			
Bearing	maintenance-free		-	
Reference surface sound pressure level DIN EN ISO 2151	< 44		dB (A)	
Voltage	230		V	
Frequency	50/60		Hz	
Rotation speed	1500		min ⁻¹	
Motor power	180		w	
Operating mode	S 1			
Type of protection DIN EN 60529	IP 54/40] -	
Class of insulation DIN EN 600034-1	F (160°C)		1	
Weight net/(gross)	11.2/(13.0)		kg	
Dimensions W/D/H	250 / 270 / 190		mm	

Accessories:						
5.7	Vacuum Control Box Model: VCpro 601 for measuring and regulation of vacuum Order no. 600100	0	Vacuum Regulator with dial gauge Model: DBR-A with hose nozzle DN 8, Connection: G1/4" - M12 x 1 to pressure adjustment - suction side Order no. 700458			
	Vacuum hose, Rubber 18 / 8 x 5 mm Order no. 828310-4		Exhaust silencer Connection: 1/8* Order no. 829901			



Gardner Denver Thomas GmbH Am Vogelherd 20 98693 Ilmenau Germany T +49 3677 604 0 F +49 3677 604 131 welch.emea@irco.com www.welchvacuum.com Customer Support +49 3677 604 0

Fax 071 7574340

We are constantly working on the further development of all our product types. Reprinting or reproduction of this manual, including extracts, is not allowed without the prior written permission of Co. Gardner Denver Thomas GmbH. All rights under the copyright laws are expressly reserved by Co. Gardner Denver Thomas GmbH. We reserve the right to make changes and amendments.

The information presented in this material is based on technical data and test results of nominal units. It is believed to be accurate and reliable and is offered as and aid to help in the selection of products. It is the responsibility of the user to determine the suitability of the product for the intended use and the user assumes all risk and liability whatsoever in connection therewith. Gardner Denver Thomas GmbH does not warrant, guarantee or assume any obligation or liability in connection with this information.

Via Vinciguerra, 45 | 62019 RECANATI MC | Tel 071 7572490